

SPECIFICATION

SSD-9319 Touchless Soap Dispenser



Specification	Specification Details	Content
	1.1 * Warranty/ Lifetime	150,000 cycles
	1.2 Battery Lifetime	More than 10,000 cycles
	1.3 Activated Method	Automatic Infrared Sensor
Ambiance	2.1 Ambient Temp. Range	4~50 degree C
	2.2 Ambient Humidity Range	20~90%
Appearance	3.1 Net weight	About 420 g
	3.2 Apperance	Exposure
	3.3 Enclosure Dimensions	96Wx190Hx103.5D
	3.4 Enclosure Material	PC
	3.5 Water & Humidity Resistance	IPX4
	3.6 Enclosure & Surface Color	White, Black, Gray,.....
	3.7 Cover Open Tool	By hand without tool
	3.8 Installation/Tool	Screwdriver
Electronic	4.1 Power type	DC
	4.2 Power Specification (power input)	DC 6V
	4.3 Battery Type/Numbers	Alkaline AA x 4
	4.4 Stand-by Current	Less than 100 uA
	4.5 Active Current	Less than 500 mA when activating
	4.6 Adjustable Sensing Distance	6~10cm
	4.7 Adjustable Sensing Range	Automatic Adjustable
	4.8 Required Sensing Time for Operation	0.5 ~ 1 sec
	4.9 LED Indicator	LED ON when sensing an object
	4.10 Low battery light	Constant LED light
Soap Specification	5.1 Soap Supply Type	Bulk fill / Refill
	5.2 Adjustable for Supply Volume	One type, Unadjustable
	5.3 Supply Volume	About 0.8ml~1.4ml
	5.4 Capacity	700ml
	5.5 PH Range	PH Range
	5.6 Dispenser Way	Drop Type
	5.7 Viscosity	1~3500 mPa.S (Remark 1)

Remark 1: Water : 1mPa.s, Alcohol : 3mPa.s, Salad Oil : 50mPa.s

2: Specifications are subject to change without notice.

*2-year limited warranty with 200 activations per day

[Solomon Technology Corp.](http://www.solomon.com.tw)

Hygiene Business Unit

e-mail : hygiene@solomon.com.tw

3F, No.42, Sing-Zhong Rd., Nei-Hu 114, Taipei, Taiwan

Tel:886-2-8791 8989 Fax:886-2-2796 2264

<http://www.solomon.com.tw/hbu>